

# EVERCOAT®

INNOVATIVE SOLUTIONS  
THAT PERFORM.

## EASY SAND

Self-levelling  
stopper



EASY SAND



The very latest filler technology

Self-levelling

Fast repair of small dents and damage

Eliminates pin-holes  
and heavy sand scratches

Ideal for smart and spot repair

Even, pin-hole free  
application of material

# 101669 – 880 ml

Easy Sand is a next generation self-levelling filler stopper. The product has been specially formulated to reduce the working time and speed up the repair process without any concession to quality. It contains special ingredients that reduce the heat generated by sanding, allowing a faster sanding process without clogging the paper.

Due to its exceptional self-levelling properties, it is ideal for the effective repair of hail damage over large areas.

The direct application over abraded OEM paint keeps the repair area relatively small. This speeds up the repair of stone-chips, dents, micro-pinholes as well as deep sand scratches. Easy Sand is therefore the ideal product for all smart and spot repair applications

*Test it yourself and experience  
the many advantages it brings  
to your repair process!*

<b>DESCRIPTION AND APPLICATION</b>	<b>FOR PROFESSIONAL USE ONLY</b> Self-levelling polyester stopper for the filling and levelling of small areas of damage such as stone-chips, dents, scratches, sanding marks, micro-pinholes and for large areas of hail damage.	
<b>SUBSTRATES</b>	Exceptional adhesion to a variety of suitably abraded substrates including; OE paint & clearcoat, steel, galvanised steel, zinc coated steel, aluminium, composite plastics, hard plastics, SMC, polyester filler.	
<b>PREPARATION</b>	Before sanding, thoroughly clean the area to be repaired removing all traces of dirt, oil and wax residues. Lightly abrade the repair area to key the surface. Use a fine abrasive to remove any deep or heavy scratch pattern. Remove the dust. The area to be repaired must be completely dry before application of product.	
<b>MIXING</b>	The mixing ratio is 2% by weight. Place the required amount of hardener on a clean, grease free, mixing board and add the requisite 2% hardener. Thoroughly mix the material to a consistent, homogenous mass that is one uniform colour. Only use the EVERCOAT hardener provided.	
<b>APPLICATION</b>	First, apply a very thin layer of mixed material with firm pressure to the repair area. This promotes an optimum, pin-hole free application and excellent adhesion. Increase to the desired depth of repair by applying layers of product. Do not apply over freshly coated surfaces or coated surfaces that have not completely cured. Allow to dry completely before finishing.	
<b>SANDING</b>	Usually the sanding process can begin after 10-5 mins. Abrade the stopper with P120 – P240 grit, avoiding deep sand scratches outside of the repair area.	
<b>TECHNICAL DATA</b>	Colour	white
	Physical State	liquid
	Solubility	not soluble in cold and warm water
	Working time	5-6 minutes
	Dry to sand time	10-15 minutes
	Corrosion Protection	n/a
	Maximum build	3 mm (sanded)
	Ingredients and Precautions	Safety data sheet (MSDS) available on request
	VOC	EU limit for volatile organic compounds: 250 g/l (2007) This product contains max 97 g/l VOC.
	The properties are typical values and not to be considered as technical sales specifications. The physical test was at about 25 °C and 75 % relative humidity unless otherwise specified.	
<b>STABILITY</b>	<b>Best before date: 18 month from manufacturing date</b> The manufacturing date is within the batch-identification number on the bottom of the can or on the label. The batch-identification is composed as follows: 8 10 233 8 = year 2018   10 = month October   233 = running batch number	
<b>STORAGE</b>	According to the requirements of local regulations. Observe the precautionary statements given on the label. Maximum storage temperature 25 °C. Store in a cool, well-ventilated place away from incompatible materials and sources of ignition. Keep away from oxidising agents, strong alkalis and acids. Smoking is prohibited in the immediate vicinity. Prevent unauthorized access. Opened containers should be closed carefully and tightly. Keep upright to prevent leakage. Do not empty into drains. Do not return mixed material to the original container.	
<b>SAFETY INSTRUCTIONS</b>	Be sure to read all instructions and warnings before using EVERCOAT products. Safety data sheets for all materials are available online at <a href="http://www.evercoat.de">www.evercoat.de</a> .	

# 101669 – 880 ml

Your EVERCOAT partner:

**EVERCOAT | a division of Illinois Tool Works Inc.**  
**Official Importer Europe**  
 DITOMA GmbH  
 Mauserstraße 6/2  
 71640 Ludwigsburg  
 Germany  
 T: +49 7141 99055 - 0  
 F: +49 7141 99055 - 22  
 E: [evercoat@ditoma.de](mailto:evercoat@ditoma.de)